EAST COAST DATA COMM (ECD)

232-X21

Overview

CapacityOne DCE RS-232 and one X.21 Sync DTE deviceInterfaceRS-232 and X.21 Male or Female connectorsData RatesUp to 128KbpsData FormatData transparent at all data ratesSwitchesNoneRS-232 Physical InterfaceMale DB-25 ConnectorX.21 Physical InterfaceFemale or Male DB-15 ConnectorPower SourceLine Powered from existing equipment - Draws 10ma - No AC power requiredEnvironmentalOperating Temperature32° to 122° F (0° to 50° C) Relative Humidity 0 to 10,000 feetDimensionsHeight 0.50 inches (1.27 cm) Width 1.75 inches (4.44 cm) Length 1.75 inches (4.44 cm)Weight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F	Application	RS-232 to X.21 Interface and Signal Level Conversion
InterfaceRS-232 and X.21 Male or Female connectorsData RatesUp to 128KbpsData FormatData transparent at all data ratesSwitchesNoneRS-232 Physical InterfaceMale DB-25 ConnectorX.21 Physical InterfaceFemale or Male DB-15 ConnectorPower SourceLine Powered from existing equipment - Draws 10ma - No AC power requiredEnvironmentalOperating Temperature32° to 122° F (0° to 50° C) Relative Humidity 0 to 10,000 feetDimensionsHeight 0.50 inches (1.27 cm) Width 1.75 inches (4.44 cm) Length 1.75 inches (4.44 cm)Weight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21		Ŭ
Data RatesUp to 128KbpsData FormatData transparent at all data ratesSwitchesNoneRS-232 Physical InterfaceMale DB-25 ConnectorX.21 Physical InterfaceFemale or Male DB-15 ConnectorPower SourceLine Powered from existing equipment - Draws 10ma - No AC power requiredEnvironmentalOperating Temperature32° to 122° F (0° to 50° C) Relative Humidity 0 to 10,000 feetDimensionsHeight 0.50 inches (1.27 cm) Width 1.75 inches (4.44 cm) Length 1.75 inches (4.44 cm)Weight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyModel: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21		
Data FormatData transparent at all data ratesData FormatData transparent at all data ratesSwitchesNoneRS-232 Physical InterfaceMale DB-25 ConnectorX.21 Physical InterfaceFemale or Male DB-15 ConnectorPower SourceLine Powered from existing equipment - Draws 10ma - No AC power requiredEnvironmentalOperating Temperature32° to 122° F (0° to 50° C) Relative Humidity 5 to 95% Non-Condensing Altitude 0 to 10,000 feetDimensionsHeight 0.50 inches (1.27 cm) Width 1.75 inches (4.44 cm) Length 1.75 inches (4.44 cm)Weight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21	Interface	RS-232 and X.21 Male or Female connectors
SwitchesNoneRS-232 Physical InterfaceMale DB-25 ConnectorX.21 Physical InterfaceFemale or Male DB-15 ConnectorPower SourceLine Powered from existing equipment - Draws 10ma - No AC power requiredEnvironmentalOperating Temperature32° to 122° F (0° to 50° C) Relative Humidity 0 to 10,000 feetDimensionsHeight 0.50 inches (1.27 cm) Width 1.75 inches (4.44 cm) Length 1.75 inches (4.44 cm)Weight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21	Data Rates	Up to 128Kbps
RS-232 Physical InterfaceMale DB-25 ConnectorX.21 Physical InterfaceFemale or Male DB-15 ConnectorPower SourceLine Powered from existing equipment - Draws 10ma - No AC power requiredEnvironmentalOperating Temperature32° to 122° F (0° to 50° C) Relative Humidity 5 to 95% Non-Condensing Altitude 0 to 10,000 feetDimensionsHeight 0.50 inches (1.27 cm) Width 1.75 inches (4.44 cm) Length 1.75 inches (4.44 cm)Weight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21	Data Format	Data transparent at all data rates
InterfaceFemale or Male DB-15 ConnectorX.21 Physical InterfaceFemale or Male DB-15 ConnectorPower SourceLine Powered from existing equipment - Draws 10ma - No AC power requiredEnvironmentalOperating Temperature32° to 122° F (0° to 50° C) Relative Humidity 5 to 95% Non-Condensing Altitude 0 to 10,000 feetDimensionsHeight 0.50 inches (1.27 cm) Width 1.75 inches (4.44 cm) Length 1.75 inches (4.44 cm)Weight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21	Switches	None
Power SourceLine Powered from existing equipment - Draws 10ma - No AC power requiredEnvironmentalOperating Temperature32° to 122° F (0° to 50° C) Relative Humidity 5 to 95% Non-Condensing Altitude 0 to 10,000 feetDimensionsHeight 0.50 inches (1.27 cm) Width 1.75 inches (4.44 cm) Length 1.75 inches (4.44 cm)Weight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21	,	Male DB-25 Connector
Draws 10ma - No AC power requiredEnvironmentalOperating Temperature32° to 122° F (0° to 50° C) Relative Humidity5 to 95% Non-Condensing Altitude0 to 10,000 feetDimensionsHeight 0.50 inches (1.27 cm) Width 1.75 inches (4.44 cm) Length 1.75 inches (4.44 cm)Weight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21	X.21 Physical Interface	Female or Male DB-15 Connector
Initial and the second state of the second state o	Power Source	
Altitude0 to 10,000 feetDimensionsHeight 0.50 inches (1.27 cm) Width 1.75 inches (4.44 cm) Length 1.75 inches (4.44 cm)Weight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21	Environmental	Operating Temperature32° to 122° F (0° to 50° C)
DimensionsHeight 0.50 inches (1.27 cm) Width 1.75 inches (4.44 cm) Length 1.75 inches (4.44 cm)Weight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21		Relative Humidity5 to 95% Non-Condensing
Width1.75 inches (4.44 cm)LengthLengthWeight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21		Altitude 0 to 10,000 feet
Length 1.75 inches (4.44 cm)Weight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21	Dimensions	Height 0.50 inches (1.27 cm)
Weight1/2 pound (0.228Kg), Includes Cable and Shipping BoxWarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21		Width 1.75 inches (4.44 cm)
WarrantyThree Years, Return to FactoryOrdering Information:Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21		Length 1.75 inches (4.44 cm)
Ordering Information: Model: 232-X21 M/F Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21	Weight	1/2 pound (0.228Kg), Includes Cable and Shipping Box
Description: RS-232 to X.21 Converter, Male DB-25 an Female DB-15 Model: 232-X21 M/M Description: RS-232 to X.21	Warranty	Three Years, Return to Factory
	Ordering Information:	Description: RS-232 to X.21 Converter, Male DB-25 and
		, , ,
Included with each unit: 1) Installation Guide	Included with each unit:	1) Installation Guide
2) 6 foot cable		2) 6 foot cable

East Coast Datacomm products have been designed to comply with the following Approvals: UL, CSA, CE, CCC, FCC. Prior to connection to any Australian telecommunication network, applicable product Certification is required.

Dataplex can assist in obtaining a connection rule from ACMA

Please note: Do not connect this item to any telecommunications network or facility unless:

1. you have the written consent of the network or facility manager or

2. the connection is in accordance with a connection permit issued for this item or

3. a connection rule for this item has been made by the Australian Communications and Media Authority.

The connection of this item to any telecommunications network or facility may cause a hazard or damage to the network or facility, or to users of the network or facility, and may result in you being consequentially liable to pay substantial compensation.